

### AMENDMENTS TO THE CLAIMS

The following listing of claims will replace all prior versions, and listings of claims in the application:

#### LISTING OF CLAIMS:

Claim 9 (Currently amended): A cartridge for ~~various wide staples used in said a~~ hammer-type stapler ~~with cartridge could load various size staples~~ comprising:

a pair of ~~two identical, upper and lower~~ substantially congruent staple containers, consisting essentially of an upper staple container and a lower staple container, each of said substantially congruent staple containers formed opposite with an upper top surface and a lower top surface respectively and contiguously positioned in symmetric opposition to each other, ; and,

a staple pusher mounted therein, ;

wherein each of said pair of substantially congruent staple containers comprises:

~~; said staple containers including~~

a pair of parallel tracks ~~protruded~~ fixedly mounted on and protruding from each ~~opposite an inner aspect of said upper and lower top surface therein surfaces and~~ thus defining therethrough an E-shaped groove, and ; a staple pusher slidably mounted on said tracks for pushing a plurality of staples loaded thereon onto said pair of parallel tracks on which the staple pusher is mounted for biasing and advancing said staples toward a staple-outlet end of the staple container, said staple pusher having including a

~~staple-like~~ shell with a staple-shaped cross-sectional profile and a block fixedly mounted on an internal bottom surface of said shell; ~~said staple container having~~

a sealer formed on an end opposite said staple-outlet end thereof for preventing ~~said the~~ staple pusher slipped off from moving past the staple-outlet end exterior the staple cartridge; ~~two staple outlets~~

a staple-outlet respectively formed on two ends thereof, at said staple-outlet end; two

a steel pad respectively mounted on said staple outlets, staple-outlet; wherein said block match is aligned with said steel pad so as to prevent result in said staple pusher not projected out from projecting exterior to said staple-outlet, and,

~~two~~ a metal coverings covering respectively pivoted pivotally mounted on two said staple-outlet end to prevent any of said plurality of staples from slipping out of the cartridge when the metal covering is in a closed position, thereof; said metal covering including wherein the metal covering comprises:

~~two~~ a pair of lateral surfaces respectively bended joined at right angles to from said a respective side distal portion of the metal covering thereof, whereby the distance between said pair of lateral surfaces is adapted to accommodate a plurality of staples of a specific width chosen from the group of pre-determined staple widths;

a front hood formed between said two lateral surfaces adjacent to ~~said staple-outlet~~, and ;

an upper opening formed above the front hood so as to  
accommodate said staple-outlet end of the staple-container and permit a driving  
element of said hammer-type stapler to be guided up and down to forcibly eject  
said plurality of staples one at a time; ~~said front hood could having two and,~~

a pair of protruding ears respectively formed respectively on  
~~two ends of~~ said lateral surfaces to facilitate pivotally moving said metal covering  
~~;~~ ~~whereby exactly guided said driving element to drive staples, and prevented~~  
~~staples slipped off said staple outlet, so that by setting a width of said lateral~~  
~~surfaces adapted to different staples, said cartridge for various wide staple could~~  
~~accommodate to staples of different width .~~

Claim 10 (Currently amended): A cartridge ~~for various wide staples used in said~~  
~~hammer-type stapler with cartridge~~ as claimed in claim 9, wherein said hammer-type  
stapler ~~with cartridge~~ has a cartridge matching unit that includes as a concave groove  
formed on ~~said a~~ front wall of ~~said a~~ hammer casing, ~~with~~ said groove having a thickness  
~~thereof about equaled~~ substantially equal to a thickness of said metal covering for  
~~matching two~~ adapting said ends of ~~said the~~ cartridge ~~for various wide~~ to accommodate  
staples of various predetermined widths; ~~whereby could laterally fix said cartridge for~~  
~~various wide staples and let~~ so that the driving unit ~~smoothly move~~ moves smoothly in  
when in juxtaposition with said metal covering.

Claim 11 (Currently amended): A cartridge ~~for various wide staples used in said hammer-type stapler with cartridge~~ as claimed in claim 9, wherein said hammer-type stapler ~~with cartridge~~ has a cartridge holder ~~including~~ comprising:

a holding flange that protrudes horizontally ~~protruded~~ from a bottom thereof; ;

a penetrating hole formed therein; ~~to~~, and,

a sliding groove crosscutting therein and vertical to said penetrating hole;

wherein said holding flange ~~could be~~ consists essentially of a thin slice of metal ~~affixed on~~ fixedly attached to a bottom of said cartridge holder for ~~holding~~ retaining said cartridge.